

VYR-5300 Rain Runner



INCLUDED



VYR-5300 Rain Runner · Hydraulic Irrigation Traveller

GENERAL PROPERTIES:

- Automatic sprinkler cart with 120 m / 394 ft of cable.
- Connection for 3/4" male or 1" female sprinklers. (SEE SPRINKLER OPTIONS).
- Automatic shut-off system with safety valve after irrigation has been completed.
- Made of aluminium, plastic and stainless steel.
- Used in full coverage irrigation with medium-high flows.

TECHNICAL SPECIFICATIONS:

- Diameter Reach: 16 - 24 m / 2-79 ft of radius.
- Flow: 2.240 - 7.840 l/h / 590 - 2070 GPH
- Working pressure: 3.5 - 6.5 BAR / 51 - 94 PSI
- Area: Part or full circle.
- Nozzles: 5-9 L/min, according to sprinkler model used and velocity!
- Trajectory angles: 28° - 30°
- Maximum stream height: 3.5 m / 11,5 ft.
- Speed: 10-20 m/h / 33-66 ft/h

APPLICATIONS:

- Sports fields and flat meadows.

DIMENSIONS:

- Length: 77 cm / 30 in
- Height: 40 cm / 16 in
- Width: 47 cm / 18,5 in
- Weight: 33 Kg / 73 Lbs

OPTIONS:

- Set with built-in sprinkler according to recommended models.
- Hose 1" for operating on our travelling sprinkler cart VYR-5300.

MODELS:

- **Ref. 005300** Rain-Runner Irrigation cart.

VYR-5300 RAIN RUNNER

- The Irrigation Traveller VYR-5300 "RAIN-RUNNER" is ideal for irrigation support in zones 1 to 8 hectares (1000-8000 m²). The power system by a water turbine allows us to leave the system running with auto scroll without having to rely on mobile tripods. Besides his constant speed ensures a perfect distribution of irrigation uniformity. Once the irrigation line is completed, a security valve will close automatically without anyone having to be aware of closing the supply valve.
- Save time and money with this innovative irrigation system, ideal for sports fields, parks, cemeteries, campuses and schools, shopping and even industrial use.

